

University of Groningen

Practical encoders for controlling nonlinear systems under communication constraints

Persis, Claudio De; Nešić, Dragan

Published in:

Proceedings of the 44th IEEE Conference on Decision and Control, and the European Control Conference 2005

IMPORTANT NOTE: You are advised to consult the publisher's version (publisher's PDF) if you wish to cite from it. Please check the document version below.

Document Version

Publisher's PDF, also known as Version of record

Publication date:

2005

[Link to publication in University of Groningen/UMCG research database](#)

Citation for published version (APA):

Persis, C. D., & Nešić, D. (2005). Practical encoders for controlling nonlinear systems under communication constraints. In *Proceedings of the 44th IEEE Conference on Decision and Control, and the European Control Conference 2005* (pp. 434-439). University of Groningen, Research Institute of Technology and Management.

Copyright

Other than for strictly personal use, it is not permitted to download or to forward/distribute the text or part of it without the consent of the author(s) and/or copyright holder(s), unless the work is under an open content license (like Creative Commons).

The publication may also be distributed here under the terms of Article 25fa of the Dutch Copyright Act, indicated by the "Taverne" license. More information can be found on the University of Groningen website: <https://www.rug.nl/library/open-access/self-archiving-pure/taverne-amendment>.

Take-down policy

If you believe that this document breaches copyright please contact us providing details, and we will remove access to the work immediately and investigate your claim.

Downloaded from the University of Groningen/UMCG research database (Pure): <http://www.rug.nl/research/portal>. For technical reasons the number of authors shown on this cover page is limited to 10 maximum.

Practical encoders for controlling nonlinear systems under communication constraints

Claudio De Persis and Dragan Nešić

Abstract—We introduce a new class of dynamic encoders for continuous-time nonlinear control systems which update their parameters only at discrete times. We prove that the information reconstructed from the encoded feedback can be used to deliver a piece-wise constant control law which yields semi-global practical stability. The result is achieved by assuming a property weaker than asymptotic stabilizability.

I. INTRODUCTION

Controlling (nonlinear) systems via encoded feedback is of paramount importance in distributed control systems. For systems of the form

$$\dot{x} = f(x, u), \quad x \in \mathbb{R}^n, \quad u \in \mathbb{R}^m \quad (1)$$

it has been very recently illustrated in the literature ([30], [18], [5]) how to design dynamic encoders which incorporate the model of the system,

$$\dot{\bar{x}}(t) = f(\bar{x}(t), u(t)) \quad (2)$$

for $t \in [kT, (k+1)T)$ and $k \in \mathbb{Z}_+$, with a discrete reset of the state, that is

$$\bar{x}(kT) = \hat{x}(kT), \quad (3)$$

and a discrete update of another fundamental parameter, namely the range of the quantization region (see below)

$$\ell((k+1)T) = \Lambda \ell(kT). \quad (4)$$

These encoders are able to guarantee (semi-)global asymptotic stabilization via encoded feedback by assuming standard stabilizability. The result relies on – among other things – showing that the encoded feedback $\bar{x}(\cdot)$ is actually an asymptotic estimate of the state $x(\cdot)$. We will not explain in detail the functioning of (2)-(4), for which the reader is referred to [30], [18], [5] (for other contributions on control via encoded or quantized feedback, the reader is referred to the important papers [20], [29], [2], [6], [25], [11], [7], [17], [21], [16], [19], [15], [14], [8], [26], [10], to name a few). Nevertheless, a brief description of the quantities in (2)-(4) will be useful later on.

The two equations (2), (3) define a nonlinear jump system used to compute the evolution of the center of the quantization region (which here, for the sake of simplicity, is chosen

to coincide with a cube). At time kT , $k \in \mathbb{Z}_+$, the center is taken equal to ([30], [18]) $\bar{x}(kT^-) := \lim_{t \rightarrow kT^-} \bar{x}(t)$, with $\bar{x}(0^-) := 0$. Each edge of the quantization region at time kT has length $2\ell(kT)$. Under the assumption that $|x(0)|_\infty \leq X$, for some $X > 0$, setting $\ell(0) = X$, the initial state is guaranteed to belong to the quantization region. Suppose this is true for all the times, that is

$$|x(kT) - \bar{x}(kT^-)|_\infty \leq \ell(kT) \quad (5)$$

for each $k \in \mathbb{Z}_+$. Then, denoted by B the integer representing the number of quantization levels used per each state component, and by $\hat{x}(kT)$ the quantized version of $x(kT)$ (see [30], [18], [5]), we have

$$|x(kT) - \hat{x}(kT)|_\infty \leq \ell(kT)/B \quad (6)$$

for each $k \in \mathbb{Z}_+$.

The actual adoption of devices such as those described above in distributed control systems very much depends on the possibility of easing the computational burden involved in the solution of (2). In this note, we address such issues by proposing encoders which do not require a continuous update of their state and which are able to reconstruct an asymptotically practically correct estimate of the state starting from encoded information. We also illustrate the possibility of using this estimate to the purpose of stabilizing the system. In particular, we discuss here an approach to achieve practical stabilizability under an assumption weaker than asymptotic stabilizability. The approach discussed in this paper can also be viewed as a general framework in which many of the results available for quantized discrete-time systems can be interpreted or even translated for continuous-time systems, although this is not discussed here in detail. Other approaches are possible [22]. We mention dwell-time switching control laws to cope with the stabilization problem under limited data rate constraints [11], [10]. They represent a durable solution to the problem, due to the simplicity of its implementation. In the next section, we consider an *approximate* discrete-time version of the system (1) and design a simplified version of the encoder (2)-(4). Two solutions are proposed, each one with its distinguishing features. In both cases, we prove that the estimate of the state $x(\cdot)$ generated by the encoder is asymptotically practically correct at the sampling times. In Section III, we extend these results to the case in which only partial-state measurements are available. In Section IV, basically under the asymptotic controllability assumption, we study the evolution of system (1) in closed-loop with a piece-wise constant control law designed on the basis of the feedback generated by the encoders examined in Sections

The work of the second author has been supported by the Australian Research Council under the Australian Professorial Fellow and Discovery Grant schemes.

Claudio De Persis is with the Dipartimento di Informatica e Sistemistica “A. Ruberti”, Università di Roma “La Sapienza”, Via Eudossiana 18, 00184 Roma, Italy depersis@dis.uniroma1.it.

Dragan Nešić is with the Department of Electrical and Electronic Engineering, The University of Melbourne, Parkville 3052, Victoria, Australia d.nesic@ee.mu.oz.au.

II and III.

Most of the proofs are omitted for lack of space.

II. A CONSISTENT DISCRETIZED ENCODER

Under piece-wise constant control laws, let us introduce as in [1] the exact discrete-time model of (1), that is

$$x((k+1)T) = f_T^e(x(kT), u(kT)) \quad (7)$$

with

$$f_T^e(x(kT), u(kT)) = x(kT) + \int_{kT}^{(k+1)T} f(x(s), u(kT)) ds. \quad (8)$$

This model is in general not available, and an approximate discrete-time model¹

$$x^a((k+1)T) = f_T^a(x^a(kT), u(kT)), \quad (9)$$

must instead be taken into account. Following [23], [1], we consider approximate models (9) which are consistent with the exact model (7):

Assumption 1: The model $f_T^a(x, u)$ is consistent with $f_T^e(x, u)$, that is for each compact set $\Omega \subset \mathbb{R}^n \times \mathbb{R}^m$, there exists a class- \mathcal{K} function $\varrho(\cdot)$ and a constant $T_0 > 0$ such that for all $(x, u) \in \Omega$ and all $T \in (0, T_0]$,

$$|f_T^e(x, u) - f_T^a(x, u)|_\infty \leq T\varrho(T).$$

Remark. Conditions under which model consistency holds are thoroughly discussed in [22], [1].

Inspired by [30], [18] and [3], we propose the following discrete-time implementation of the encoder (2)-(4):

$$\begin{aligned} \bar{x}((k+1)T) &= f_T^a(\hat{x}(kT), u(kT)) \\ \ell((k+1)T) &= \Lambda \ell(kT) + T\varrho(T), \end{aligned} \quad (10)$$

with $\Lambda > 0$ a constant to design. As recalled in the previous section, vector $\hat{x}(kT)$ is such that $|\hat{x}(kT) - x(kT)|_\infty \leq \ell(kT)/B$, whenever $|\bar{x}(kT) - x(kT)|_\infty \leq \ell(kT)$.

Assume the following ([3]):

Assumption 2: For any pair of constants $X > 0$ and $U > 0$, there exists a number $Y > 0$ such that, if $|x(0)|_\infty \leq X$ and $|u(kT)|_\infty \leq U$ for each $k \in \mathbb{Z}_+$, then $|x(kT)|_\infty \leq Y$ for each $k \in \mathbb{Z}_+$, where $x(kT)$ is the solution of (1) at time kT .

The result below shows a clear relation between the degree of accuracy achievable by the “asymptotic estimate” $\hat{x}(\cdot)$ of $x(\cdot)$, the parameter B and the sampling period T . It relies on the concept of consistency ([23], [1]) recalled above and employs arguments inspired by those in [3], proof of Proposition 1. In the statement, the symbol $\mathcal{C}_r(s)$, with $r > 0$ an integer and $s > 0$ a real number, denotes the cube in \mathbb{R}^r centered around the origin and with edges of length $2s$.

¹For the sake of conciseness, we do not consider in this note the presence of the “modelling parameter” δ [22], [1], but the conclusions we draw hold analogously for the case in which δ is present. The parameter δ plays a fundamental role for further developments of our approach to the design of encoders, for it allows to improve the accuracy of the approximate discrete-time model without affecting the data rate.

Proposition 1: Let Assumptions 1 and 2 hold. Then for any $X > 0$ and for any $U > 0$ we can find $T^* > 0$ with the property that, for all $T \in (0, T^*]$, $|x(0)|_\infty \leq X$ implies

$$|x(kT) - \hat{x}(kT)|_\infty \leq \Lambda^k \frac{X}{B} + \frac{1}{B - F^a} T\varrho(T),$$

provided that $\bar{x}(0) = 0$, $\ell(0) = X$, $\Lambda := F^a/B$, and $B > F^a + 1$, with $F^a > 0$ the Lipschitz constant for which

$$|f_T^a(x, u) - f_T^a(\hat{x}, u)|_\infty \leq F^a |x - \hat{x}|_\infty$$

for all $(x, u), (\hat{x}, u) \in \mathcal{C}_n(X + Y + T\varrho(T)) \times \mathcal{C}_m(U)$.

Proof: In Assumption 1, let Ω be $\mathcal{C}_n(Y) \times \mathcal{C}_m(U)$ and fix $\varrho(\cdot)$ and T_0 accordingly. Set $T^* = T_0$ and fix $T \in (0, T^*]$. Note that $|x(0)|_\infty \leq X$, $\bar{x}(0) = 0$ and $\ell(0) = X$ imply $|\hat{x}(0)|_\infty \leq X$ and $|x(0) - \hat{x}(0)|_\infty \leq X/B$. Assume that, for some $k \in \mathbb{Z}_+$, $|x(jT) - \bar{x}(jT)|_\infty \leq \ell(jT)$ and $|x(jT) - \hat{x}(jT)|_\infty \leq \ell(jT)/B$ for each $j = 0, 1, \dots, k$. In particular, (5) (with $\bar{x}(kT^-)$ replaced by $\bar{x}(kT)$) and (6) hold. The evolution of $\ell(\cdot)$ as given by the second equation in (10) is described by the relation

$$\begin{aligned} \ell(kT) &= \Lambda^k \ell(0) + \sum_{j=0}^{k-1} \Lambda^{k-1-j} T\varrho(T) \\ &= \Lambda^k X + \frac{1 - \Lambda^k}{1 - \Lambda} T\varrho(T). \end{aligned}$$

Hence,

$$\frac{\ell(kT)}{B} \leq \Lambda^k \frac{X}{B} + \frac{1}{B - F^a} T\varrho(T).$$

As $|x(kT)|_\infty \leq Y$ for all $k \in \mathbb{Z}_+$, relation (6) guarantees that $|\hat{x}(kT)|_\infty \leq \ell(kT)/B + Y \leq X + Y + T\varrho(T)$. Consider now the following chain of relations:

$$\begin{aligned} |x((k+1)T) - \bar{x}((k+1)T)|_\infty &= \\ |f_T^e(x(kT), u(kT)) - f_T^a(\hat{x}(kT), u(kT))|_\infty &= \\ |f_T^e(x(kT), u(kT)) - f_T^a(x(kT), u(kT)) + \\ f_T^a(x(kT), u(kT)) - f_T^a(\hat{x}(kT), u(kT))|_\infty &\leq \\ T\varrho(T) + F^a |x(kT) - \hat{x}(kT)|_\infty &\leq T\varrho(T) + F^a \ell(kT)/B = \\ \Lambda \ell(kT) + T\varrho(T) = \ell((k+1)T). \end{aligned}$$

This implies that $x((k+1)T)$ belongs to the quantization region at time $(k+1)T$, and hence $|x((k+1)T) - \hat{x}((k+1)T)|_\infty \leq \ell((k+1)T)/B$. By induction we conclude that both (5) and (6) hold for each $k \in \mathbb{Z}_+$. Bearing in mind that $\Lambda < 1$ and (6), we obtain

$$|x(kT) - \hat{x}(kT)|_\infty \leq \Lambda^k \frac{X}{B} + \frac{1}{B - F^a} T\varrho(T),$$

that is the thesis. \blacksquare

Allowing a more complex dynamics for the encoder, it is possible to remove the presence of the term $T\varrho(T)$. This can be done under the following assumption [23]:

Assumption 3: For each compact set $\Omega \subset \mathbb{R}^n \times \mathbb{R}^m$, there exist $K > 0$ and $T^* > 0$ such that, for all (x, u) and (z, u) in Ω , and all $T \in (0, T^*]$,

$$|F_T(x, u) - F_T(z, u)| \leq (1 + KT)|x - z|,$$

where F_T is either f_T^a or f_T^e .

We recall the following result (cf. Lemma 2, Lemma 3 and Remark 2 in [23]), which states that model consistency propagates through arbitrarily large intervals of time:

Lemma 1: Let Assumptions 1, 2, and 3 hold. Then, for any $X > 0$, $U > 0$, $L > 0$ and $\eta > 0$, there exists $\hat{T} > 0$ such that $T \in (0, \hat{T}]$ and $x(0) = x^a(0)$ imply

$$|x(kT) - x^a(kT)| \leq \eta, \quad \forall k : kT \in [0, L].$$

The proposed modified encoder is as follows:

$$\begin{aligned} x^a((k+1)T) &= f_T^a(x^a(kT), u(kT)) \\ \bar{x}((k+1)T) &= f_T^a(\hat{x}(kT), u(kT)) \\ \ell((k+1)T) &= \Lambda \ell(kT), \end{aligned} \quad (11)$$

Remark. The decoder will implement only the last two equations of (11).

The main difference lies in the fact that it also implements the equations describing the evolution of the approximate model. Hence, in the present case, $\hat{x}(kT)$ is a vector for which (6), with $x(kT)$ replaced by $x^a(kT)$, holds, provided that (5), again with $x(kT)$ replaced by $x^a(kT)$, holds as well. Then the following result is true:

Proposition 2: Let Assumptions 1, 2, and 3 hold. Then for any $X > 0$, $U > 0$, $L > 0$ and $\eta > 0$ we can find a $T^* > 0$ with the property that, for all $T \in (0, T^*]$, $|x(0)|_\infty \leq X$ implies

$$|x(kT) - \hat{x}(kT)|_\infty \leq \Lambda^k \frac{X}{B} + \eta \quad \forall k : kT \in [0, L],$$

provided that $x^a(0) = x(0)$, $\bar{x}(0) = 0$, $\ell(0) = X$ and $\Lambda := F^a/B < 1$, with $F^a > 0$ the Lipschitz constant for which

$$|f_T^a(x, u) - f_T^a(\hat{x}, u)|_\infty \leq F^a |x - \hat{x}|_\infty$$

for all $(x, u), (\hat{x}, u) \in \mathcal{C}_n(X + Y + \eta) \times \mathcal{C}_n(U)$.

Proof: The proof is omitted for lack of space. ■

Remark. A modification of the structure of the practical encoders described in this section may lead to encoders which employ lower data rates. See [30], [19] and [4] for details.

III. OBSERVER-BASED PRACTICAL ENCODERS

The previous section has focused on the case in which full state was available for measurements. Here we consider the case in which the system (1) is endowed with a readout map which is different from the identity, namely

$$y = h(x) \in \mathbb{R}^p. \quad (12)$$

In this scenario, the design of the encoders is based on observers ([1]). A common approach to the design of sampled-data observer lies on a suitable discretization of a continuous-time observer. This is examined in the next subsection. Another approach, which typically exhibits a better performance in simulations, consists of designing the discrete-time observer directly. This approach is studied in Subsection III.B.

A. Encoder design by emulation

In this subsection, we assume that a continuous-time observer

$$\dot{\sigma}(t) = g(\sigma(t), y(t), u(t)) \quad (13)$$

is actually available, and consider its zero order hold equivalent ([13]):

$$\sigma((k+1)T) = g_T^a(\sigma(kT), y(kT), u(kT)). \quad (14)$$

Namely, we assume the following ([1]):

Assumption 4: System (14) is a semi-global practical observer, i.e. there exists a class- \mathcal{KL} function $\omega(\cdot, \cdot)$ such that, for any $X > \chi > 0$ and any $Y > 0$ and $U > 0$, we can find a $T^* > 0$ such that, for all $T \in (0, T^*]$,

$$|x(0)|_\infty \leq X, \quad |\sigma(0) - x(0)|_\infty \leq 2X,$$

and

$$|x(k)|_\infty \leq Y, \quad |u(k)|_\infty \leq U,$$

for each $k \in \mathbb{Z}_+$, imply

$$|\sigma(kT) - x(kT)| \leq \omega(|\sigma(0) - x(0)|, kT) + \chi, \quad (15)$$

for each $k \in \mathbb{Z}_+$.

Remark. There are precise conditions under which the assumption above is fulfilled, and these are investigated in [1]. Suppose the following hypotheses hold true:

- (i) The model $g_T^a(\cdot, \cdot, \cdot)$ is consistent with the model $g(\cdot, \cdot, \cdot)$.
- (ii) There exist a continuously differentiable function $V(x, \sigma)$ and class- \mathcal{K}_∞ functions $\alpha_1(\cdot)$, $\alpha_2(\cdot)$, $\alpha_3(\cdot)$ such that

$$\begin{aligned} \alpha_1(|x - \sigma|) &\leq V(x, \sigma) \leq \alpha_2(|x - \sigma|) \\ \frac{\partial V}{\partial x} f(x, u) + \frac{\partial V}{\partial \sigma} g(\sigma, y, u) &\leq -\alpha_3(|x - \sigma|). \end{aligned}$$

Then, by [1], Theorem 3, Assumption 2 implies Assumption 4.

In the sequel, it will be useful to single out a part of the observer (14) not affected by the output:

Assumption 5: Map $g_T^a(\sigma(kT), y(kT), u(kT))$ can be decomposed as

$$\begin{aligned} g_T^a(\sigma(kT), y(kT), u(kT)) &= g_{T1}^a(\sigma(kT), u(kT)) + \\ &g_{T2}^a(\sigma(kT), y(kT), u(kT)). \end{aligned}$$

Furthermore, there exist a class- \mathcal{KL} function $\tilde{\omega}(\cdot, \cdot)$ and a constant $\tilde{\chi}$ such that, $|\sigma(kT) - x(kT)| \leq \tilde{\omega}(|\sigma(0) - x(0)|, kT) + \tilde{\chi}$ implies

$$|g_{T2}^a(\sigma(kT), y(kT), u(kT))| \leq \tilde{\omega}(|\sigma(0) - x(0)|, kT) + \tilde{\chi}.$$

Remark. If $g(\cdot, \cdot, \cdot)$ is a continuously differentiable function, and the Lyapunov function in the Remark following Assumption 4 holds with $V(x, \sigma) = V(x - \sigma) =: V(e)$, then it implies that $x = \sigma$ must be an invariant manifold for system (1), (12), (13) and therefore $g(x, h(x), u) = f(x, u)$ which in turn implies [28]

$$\dot{\sigma}(t) = f(\sigma(t), u(t)) + \tilde{g}(\sigma(t), y(t), u(t))(y(t) - h(\sigma(t))),$$

with $\tilde{g}(\cdot, \cdot, \cdot)$ a suitable continuous function. Using e.g. Euler discretization for the latter system and letting $h(\cdot)$ be Lipschitz continuous, then Assumption 4 implies:

$$\begin{aligned} |g_{T2}^a(\sigma(kT), y(kT), u(kT))| &= |\tilde{g}(\sigma(kT), y(kT), u(kT)) \cdot \\ &\cdot (y(kT) - h(\sigma(kT)))| \leq \tilde{G}(\omega(|\sigma(0) - x(0)|, kT) + \chi), \end{aligned}$$

for some constant $\tilde{G} > 0$.

Following [30] (see also [24]), we propose the following observer-based encoder:

$$\begin{aligned} \sigma((k+1)T) &= g_T^a(\sigma(kT), y(kT), u(kT)) \\ \varsigma((k+1)T) &= g_{T1}^a(\varsigma(kT), u(kT)) \\ \ell((k+1)T) &= \Lambda \ell(kT) + \tilde{\omega}(2\sqrt{n}X, kT) + \tilde{\chi}. \end{aligned} \quad (16)$$

Remark. If the function $\tilde{\omega}(\cdot, \cdot)$ is not available, then it can be replaced by a suitable constant. This replacement will affect the accuracy of the encoding procedure carried out by the device (16).

Notice that, differently from the state feedback case, here the signal $\hat{\varsigma}(\cdot)$ represents not the encoded state of the process $x(\cdot)$ but the encoded state of the observer $\sigma(\cdot)$. Furthermore, $\varsigma(\cdot)$ represents the center of the quantization region. Hence, analogously to the state feedback case, $|\sigma(kT) - \varsigma(kT)|_\infty \leq \ell(kT)$ implies $|\sigma(kT) - \hat{\varsigma}(kT)|_\infty \leq \ell(kT)/B$. It is worth stressing that the decoder at the other end of the channel will implement only the last two equations in (16) ($y(\cdot)$ is not available to the decoder). Now, we introduce the constant:

$$Z := \omega(2\sqrt{n}X, 0) + \tilde{\omega}(2\sqrt{n}X, 0) + \chi + \tilde{\chi} + X + Y.$$

The main result of this subsection is as follows:

Proposition 3: Let Assumptions 2 and 4-5 hold. Then for any $X > 0$ and for any $U > 0$ we can find a $T^* > 0$ with the property that, for all $T \in (0, T^*]$, $|x(0)|_\infty \leq X$ implies

$$|x(kT) - \hat{\varsigma}(kT)|_\infty \leq \omega(|\sigma(0) - x(0)|, kT) + \chi + \ell(kT)$$

provided that $\varsigma(0) = 0$, $|\sigma(0)|_\infty \leq X$, $\ell(0) = X$, $\Lambda := G^a/B$, and $B > G^a + 1$, with $G^a > 0$ the Lipschitz constant for which

$$|g_{T1}^a(\sigma, u) - g_{T1}^a(\hat{\sigma}, u)|_\infty \leq G^a|\sigma - \hat{\sigma}|_\infty$$

for all $(\sigma, u), (\hat{\sigma}, u) \in \mathcal{C}_n(Z) \times \mathcal{C}_m(U)$.

Remark. It is easily seen that the estimation error $x(kT) - \hat{\varsigma}(kT)$ asymptotically converges to a square with edges of length $\chi + \tilde{\chi}/(B - G^a)$.

Proof: The proof is omitted for lack of space. ■

B. Encoder design by approximate discrete-time models

In this subsection, we pursue another approach to the design of practical encoders for system (1) with output map (12), namely we assume the existence of a discrete-time observer for the approximate model (9). We have [1]:

Assumption 6: System

$$\xi((k+1)T) = f_T^a(\xi(kT), u(kT)) + g_T(\xi(kT), y(kT), u(kT))$$

is a semi-global practical observer for system (1), (12), i.e. there exists a class- \mathcal{KL} function β such that, for any $0 <$

$\chi < X$ and any $Y > 0$, $U > 0$, it is possible to find a $T^* > 0$ such that, for all $T \in (0, T^*]$,

$$|x(0)|_\infty \leq X, \quad |x(0) - \xi(0)|_\infty \leq 2X,$$

and

$$|x(kT)|_\infty \leq Y, \quad |u(kT)|_\infty \leq U$$

for each $k \in \mathbb{Z}_+$, imply

$$|x(kT) - \xi(kT)| \leq \beta(|x(0) - \xi(0)|, kT) + \chi,$$

for each $k \in \mathbb{Z}_+$.

Having set

$$Z = Y + \beta(2\sqrt{n}X, 0) + \chi,$$

we pick the constant \tilde{F}^a for which

$$|f_T^a(x, u) - f_T^a(\hat{x}, u)|_\infty \leq \tilde{F}^a|x - \hat{x}|_\infty$$

for all $(x, u), (\hat{x}, u) \in \mathcal{C}_n(Z) \times \mathcal{C}_m(U)$, and set

$$\mu(r, k, T) = \beta(r, (k+1)T) + \chi + \tilde{F}^a(\beta(r, kT) + \chi) + T\varrho(T).$$

We also set $\Lambda = F^a/B$, with F^a the Lipschitz constant of $f_T^a(x, u)$ over the set $\mathcal{C}_n(\mu(2\sqrt{n}X, 0, T) + X + Z) \times \mathcal{C}_m(U)$. The encoder is as follows:

$$\begin{aligned} \xi((k+1)T) &= f_T^a(\xi(kT), u(kT)) + \\ &\quad g_T(\xi(kT), y(kT), u(kT)) \\ \bar{\xi}((k+1)T) &= f_T^a(\bar{\xi}(kT), u(kT)) \\ \ell((k+1)T) &= \Lambda \ell(kT) + \mu(2\sqrt{n}X, k, T), \end{aligned}$$

where $|\bar{\xi}(kT) - \xi(kT)|_\infty \leq \ell(kT)/B$ provided that $|\bar{\xi}(kT) - \xi(kT)|_\infty \leq \ell(kT)$.

Remark. As in the previous subsection, the decoder will implement only the last two equations above. To correctly encode the observer state ξ , the decoder needs an estimate of the term $g_T(\xi(kT), y(kT), u(kT))$. Part of the proof of the proposition below deals with deriving this estimate.

We are now ready to state the main result of this subsection:

Proposition 4: Let Assumptions 1, 2 and 6 hold. Then for any $X > 0$ and for any $U > 0$ we can find a $T^* > 0$ with the property that, for all $T \in (0, T^*]$, $|x(0)|_\infty \leq X$ implies

$$|x(kT) - \hat{\xi}(kT)|_\infty \leq \beta(|\xi(0) - x(0)|, kT) + \chi + \frac{\ell(kT)}{B}$$

provided that $\bar{\xi}(0) = 0$, $|\xi(0)|_\infty \leq X$, $\ell(0) = X$, and $\Lambda := F^a/B$, with $B > F^a + 1$.

Proof: The proof is omitted for lack of space. ■

IV. PRACTICAL STABILIZATION

The attention is now turned to the design of the controller, for which we follow very closely [12]. We shall refer to Proposition 1 for the state feedback case, and to Proposition 3, for the output feedback case. Analogous results can be given using Proposition 2 and, respectively, Proposition 4. A number of notions from [12] are now introduced. The positive numbers $r < R$ and $r_m < R_m$ are given and the symbol $\mathcal{V}(S)$ denotes the level set $\{x : V(x) \leq S\}$.

Assumption 7: There exists a continuous Lyapunov function $V(\cdot) : \mathbb{R}^n \rightarrow \mathbb{R}_+$ for which:

- There exist class- \mathcal{K}_∞ functions $\nu(\cdot), \rho(\cdot)$ such that $|V(x_1) - V(x_2)| \leq \rho(|x_1 - x_2|)$. Moreover, $V(x) \geq \nu(|x|)$.
- There exist a feedback function $\kappa(\cdot) : \mathbb{R}^n \rightarrow \mathbb{R}^m$ and constants $T > 0, c > 0$ such that the solution of $\dot{x}(t) = f(x(t), \kappa(x(0)))$ with $x(0) \in \mathcal{V}(R)$ satisfies:
(S1) $V(x(T)) \leq \max\{V(x(0)) - c, r\}$
(S2) $V(x(t)) \leq \max\{V(x(0)), r\} + r_m, \forall t \in [0, T]$.

We also introduce the following:

Assumption 8: Set $\mathcal{U} := \{u \in \mathbb{R}^m : u = \kappa(x), x \in \mathcal{V}(R + R_m)\}$.

1) There exists $M \geq 0$ such that $|f(x, u)| \leq M$ for all $x \in \mathcal{V}(R + R_m)$, for all $u \in \mathcal{U}$.

2) There exists $L_{fx}, L_{fu} > 0$ such that $|f(x_1, u_1) - f(x_2, u_2)| \leq L_{fx}|x_1 - x_2| + L_{fu}|u_1 - u_2|$, for all $x_1, x_2 \in \mathcal{V}(R + R_m)$, for all $u_1, u_2 \in \mathcal{U}$.

Remark. Assumptions 7 and 8 are discussed in [12].

We recall the following statement from [12]:

Theorem 1: Under Assumptions 7 and 8, consider

$$\dot{x}(t) = f(x(t), \kappa(x(0))) + d(t)$$

where $x(0) \in \mathcal{V}(R)$. Let $\sigma \in [0, R_m - r_m]$. If the disturbance $d(\cdot)$ satisfies

$$\max_{t \in [0, T]} \left| \int_0^t d(s) ds \right| \leq \rho^{-1}(\sigma) e^{-L_{fx} T}$$

then for all $t \in [0, T]$, the solution $x(\cdot)$ exists and satisfies

$$V(x(T)) \leq \max\{V(x(0)) - c, r\} + \sigma$$

$$V(x(t)) \leq \max\{V(x(0)), r\} + (r_m + \sigma).$$

We now apply this theorem and the results in the previous section to show practical stabilization when using the control law

$$u(t) = \kappa(\hat{x}(kT)), \quad t \in [kT, (k+1)T),$$

where the samples $\hat{x}(\cdot)$ are generated by the decoder (10). To proceed, fix $r = r_m < R, R_m$. Set

$$\nu(X) = R, \quad \nu(Y) = R + R_m, \quad U = \max_{|x|_\infty \leq Y} |\kappa(x)|_\infty,$$

so that $x \in \mathcal{V}(R)$ implies $|x| \leq X$ and $x \in \mathcal{V}(R + R_m)$ implies $|x| \leq Y$. Choose the constant F^a in Proposition 1 accordingly. Finally, in (10) set $\Lambda = F^a/B$. The result below proves that under the assumptions just stated, and despite of the quantization error, a control law exists which keeps the state confined in $\mathcal{V}(R + R_m)$, where, applying the results established in the previous section, an increasingly accurate estimation of the state is possible. Practical stability of the resulting closed-loop system is then concluded.

Proposition 5: Let Assumptions 1, 7 and 8 hold. Let $T \in (0, T_0]$ with T and T_0 as in Assumption 7 and, respectively, Assumption 1. Let $\sigma \in [0, \min\{R_m - r_m, R - r, c/4\}]$. Set

$$\frac{1}{\sqrt{n}} E_k := \Lambda^k \frac{X}{B} + \frac{1}{B - F^a} T \varrho(T), \quad k \in \mathbb{Z}_+,$$

and choose $B > F^a + 1$ so that:

$$E_0 \in \left[0, \min \left\{ \frac{\rho^{-1}(\sigma)}{2 + L_{fx} T} e^{-L_{fx} T}, \rho^{-1}(R - r - \sigma) \right\} \right). \quad (17)$$

Then, the solution of the closed-loop system

$$\dot{x}(t) = f(x(t), \kappa(\hat{x}(kT))), \quad t \in [kT, (k+1)T), \quad k \in \mathbb{Z}_+$$

from the initial condition $x(0) \in \mathcal{V}(R - 2\rho(E_0))$ exists for all $t \geq 0$ and satisfies

$$V(x(kT)) \leq \max\{V(x(0)) - \frac{(3k-1)c}{4}, r\} + \rho(E_k) + \sigma, \quad \forall k \in \mathbb{Z}_+$$

$$V(x(t)) \leq \max\{V(x(kT)) + \rho(E_k), r\} + r + \sigma + \rho(E_k), \quad \forall t \in [kT, (k+1)T), \quad \forall k \in \mathbb{Z}_+.$$

Remark. From the first inequality above, we see that the state of the closed-loop system at the sampling times asymptotically converges to the level set

$$\left\{ x \in \mathbb{R}^n : V(x) \leq r + \sigma + \rho \left(\frac{1}{B - F^a} T \varrho(T) \right) \right\}.$$

Proof: The result is an application of [12], Proposition 1, and its proof is basically the same. The differences are as follows: We explicitly take into account the fact that the “measurement noise” (i.e. the quantization error) is vanishing and we take care of the fact that the measurement noise itself is not known *a priori* unless we guarantee that the state is confined within the quantization region. For lack of space, details are omitted. ■

Mutatis mutandis, an output-feedback version of the previous result can also be stated. In the following proposition, the solution $x(\cdot)$ we refer to is the solution of the process (1) in closed loop with the “output feedback” control law:

$$u(t) = \kappa(\hat{z}(kT)), \quad t \in [kT, (k+1)T),$$

where the samples $\hat{z}(\cdot)$ are generated by the encoder (16). Fix the constants r, R, r_m, R_m and X as before, set $\nu(Y) = R + R_m$,

$$Z = \omega(2\sqrt{n}X, 0) + \tilde{\omega}(2\sqrt{n}X, 0) + \chi + \tilde{\chi} + X + Y,$$

$$U = \max_{|x|_\infty \leq Z} |\kappa(x)|_\infty,$$

and let $G^a > 0$ be such that

$$|g_{T1}^a(\sigma, u) - g_{T1}^a(\hat{\sigma}, u)|_\infty \leq G^a |\sigma - \hat{\sigma}|_\infty$$

for all $(\sigma, u), (\hat{\sigma}, u) \in \mathcal{C}_n(Z) \times \mathcal{C}_m(U)$. Also let $\Lambda = G^a/B$ in the encoder (16). Then we can state:

Proposition 6: Let Assumptions 1, and 4-8 hold. Let $T \in (0, T_0]$ with T and T_0 as in Assumption 7 and, respectively, Assumption 1.

Set

$$\begin{aligned} \frac{1}{\sqrt{n}} E_k &:= \Lambda^k \frac{X}{B} + \frac{1}{B - F^a} \tilde{\chi} + \\ &+ \sum_{j=0}^{k-1} \Lambda^{k-1-j} \frac{\tilde{\omega}(2\sqrt{n}X, jT)}{B}, \end{aligned}$$

$k \in \mathbb{Z}_+$, and choose $B > G^a + 1$ so that:

$$E_0 \in \left[0, \min \left\{ \frac{\rho^{-1}(\sigma)}{2 + L_{fx}T} e^{-L_{fx}T}, \rho^{-1}(R - r - \sigma) \right\} \right) . \quad (18)$$

Then, the solution of the closed-loop system

$$\dot{x}(t) = f(x(t), \kappa(\hat{\zeta}(kT))) , \quad t \in [kT, (k+1)T) , \quad k \in \mathbb{Z}_+$$

from the initial condition $x(0) \in \mathcal{V}(R - 2\rho(E_0))$ exists for all $t \geq 0$ and satisfies

$$\begin{aligned} V(x(kT)) &\leq \max\{V(x(0)) - \frac{(3k-1)c}{4}, r\} + \\ &\quad + \rho(E_k) + \sigma , \quad \forall k \in \mathbb{Z}_+ \\ V(x(t)) &\leq \max\{V(x(kT)) + \rho(E_k), r\} + r + \sigma + \\ &\quad + \rho(E_k) , \quad \forall t \in [kT, (k+1)T) , \quad \forall k \in \mathbb{Z}_+ . \end{aligned}$$

Proof: The proof is omitted. ■

V. CONCLUSION

The paper deals with the design of encoders for continuous-time nonlinear systems via their approximate discrete-time models. This approach has several advantages. With respect to previous dynamic encoding schemes presented in the literature, the encoder designed in this way allows to achieve (semi-global practical) stability with less computational effort. Moreover, the methods presented in the paper allow to extend the results available for the quantized control of discrete-time systems to continuous-time systems, and to overcome the drawbacks in connections with some existing methods. In the results established in the paper, decrease in sampling time improves the performance of the system. However, this may not be possible due to communication constraints. The introduction of another parameter in addition to the sampling period T allows to refine the model independently of T , and thus to achieve the same results while fulfilling the communication constraints. Although the analysis of the role of such additional parameter has not been included in the paper for lack of space, it is very important for further developments. The paper has also shown how to apply the results of [12] to the study of the robustness of nonlinear systems in the presence of quantization errors. Applications of the techniques presented in the paper to more general problems of control under communication constraints [9], [27] may represent another interesting line of research to pursue.

Acknowledgement The first author would like to thank D. Liberzon who directed his attention to the arguments discussed in the paper.

REFERENCES

- [1] M. Arçak and D. Nešić. A framework for nonlinear sampled-data observer design via approximate discrete-time models and emulation. *Automatica*, 40, 1931–1938, 2004.
- [2] R.W. Brockett and D. Liberzon. Quantized feedback stabilization of linear systems. *IEEE Trans. Aut. Contr.*, 45:1279–1289, 2000.
- [3] C. De Persis. On stabilization of nonlinear systems under data-rate constraints: The case of discrete-time systems. In *Mini-Symposium Control, Quantization and Communication Constraints*, S. Zampieri (Org.), 16th Int. Symp. on Math. Th. of Net. Syst., Leuven, Belgium, 2004.
- [4] C. De Persis. n -bit stabilization of n -dimensional nonlinear systems in feedforward form. *IEEE Trans. Autom. Contr.*, 50(3):299–311, 2005.
- [5] C. De Persis and A. Isidori. Stabilizability by state feedback implies stabilizability by encoded state feedback. *Systems & Control Letters*, 53, 249–258, 2004.
- [6] N. Elia and S.K. Mitter. Stabilization of linear systems with limited information. *IEEE Trans. Aut. Contr.*, 46(9):1384–1400, September 2001.
- [7] F. Fagnani and S. Zampieri. Stability analysis and synthesis for scalar linear systems with a quantized feedback. *IEEE Trans. Aut. Contr.*, 48(9):1569–1584, 2003.
- [8] F. Fagnani and S. Zampieri. Quantized stabilization of linear systems: Complexity versus performance. *IEEE Trans. Aut. Contr.*, 49(9):1534–1548, 2004.
- [9] D. Hristu and K. Morgansen. Limited communication control. *Systems & Control Letters*, 37:193–205, 1999.
- [10] H. Ishii and T. Başar. Remote control of LTI systems over networks with state quantization. *Systems & Control Letters*, 54:15–31, 2005.
- [11] H. Ishii and B.A. Francis. Stabilizing a linear system by switching control with dwell time. *IEEE Trans. Aut. Contr.*, 47:1962–1973, 2002.
- [12] C.M. Kellet, H. Shim, and A.R. Teel. Further results on robustness of (possibly discontinuous) sample and hold feedback. *IEEE Transactions on Automatic Control*, 49(7):1081–1089, July 2004.
- [13] D.S. Laila, D. Nešić, and A.R. Teel. Open and closed loop dissipation inequalities under sampling and controller emulation. *European Journal of Control*, 18:109–125, 2002.
- [14] K. Li and J. Baillieul. Data-rate requirements for nonlinear feedback control. In *Proc. of the 6th IFAC Symp. Nonl. Contr. Syst.*, Stuttgart, Germany, 2004.
- [15] K. Li and J. Baillieul. Robust quantization for digital finite communication bandwidth (DFCB) control. *IEEE Trans. Aut. Contr.*, 49:1573–1584, 2004.
- [16] D. Liberzon. Hybrid feedback stabilization of systems with quantized signals. *Automatica*, 39:1543–1554, September 2003.
- [17] D. Liberzon. On stabilization of linear systems with limited information. *IEEE Trans. Aut. Contr.*, 48(2):304–307, February 2003.
- [18] D. Liberzon and J.P. Hespanha. Stabilization of nonlinear systems with limited information feedback. To appear in *IEEE Trans. Aut. Contr.*, 2005. Also in *Proceedings of the 42nd IEEE Conf. Dec. Contr.*, 2003.
- [19] G. Nair, R.J. Evans, I.M.Y. Mareels, and W. Moran. Topological feedback entropy and nonlinear stabilization. *IEEE Trans. Autom. Contr.*, 49(9):1585–1597, 2004.
- [20] G.N. Nair and R.J. Evans. Stabilization with data-rate-limited feedback: Tightest attainable bounds. *Systems & Control Letters*, 41(1):49–56, September 2000.
- [21] G.N. Nair and R.J. Evans. Exponential stabilisability of finite-dimensional linear systems with limited data rates. *Automatica*, 39:585–593, 2003.
- [22] D. Nešić and A.R. Teel. A framework for stabilization of nonlinear sampled-data systems based on their approximate discrete-time systems. *IEEE Trans. Aut. Contr.*, 49:1103–1122, 2004.
- [23] D. Nešić, A.R. Teel, and P.V. Kokotović. Sufficient conditions for stabilization of sampled-data nonlinear systems via discrete-time approximations. *Systems & Control Letters*, 38:259–270, 1999.
- [24] C. De Persis. Results on stabilization of nonlinear systems under finite data-rate constraints. In *Proceedings of the 43rd Conference on Decision and Control*, Nassau, The Bahamas, pages 3986–3991, 2004.
- [25] I.R. Petersen and A.V. Savkin. Multi-rate stabilization of multivariable discrete-time linear systems via a limited capacity communication channel. In *Proceedings of the 40th Conf. on Dec. and Contr.*, pages 304–309, 2001.
- [26] B. Picasso and A. Bicchi. Control synthesis for practical stabilization of quantized linear systems. *Rendiconti del Seminario Matematico*, 2005. (in press).
- [27] B. Picasso, L. Palopoli, A. Bicchi, and K.H. Johansson. Control of distributed embedded systems in the presence of unknown but bounded noise. In *Proceedings of the 43rd IEEE Conf. on Dec. and Contr.*, pages 1448–1453, 2004.
- [28] L. Praly and M. Arcak. On certainty-equivalence design of nonlinear observer-based controllers. In *Proc. 41st IEEE Conf. Dec. Contr.*, Las Vegas, NV, USA, pages 1485–1490, 2002.
- [29] S. Tatikonda. *Control under communication constraints*. PhD thesis, MIT, August 2000.
- [30] S. Tatikonda and S. Mitter. Control under communication constraints. *IEEE Trans. Aut. Contr.*, 49:1056–1068, 2004.